



Digital RCD(ELCB) Tester

| Electrical Power

☰ Details Info

SPECIFICATIONS

Working Voltage	230V±15%Hz
Creepage Level Selection	10/20/30/200/300/500mA
Fault Action Time	Max.1000mS
Accuracy	Electric Current : ±8% Voltage : 0.6% ±4dgt
Working Temperature	0°C~40°C
Working Humidity	30~90%RH
Testing Button	√
Low Voltage Indication	√

PACKING INFORMATION

Product Net Weight	2000G
--------------------	-------

Product Size	7095Line*1pcs、7094line*1pcs、8032Iron Stick 1 Pair、R6P(AA)*6pcs、
Packing	Gift Box
Standard Quantity Per Carton	5
Standard Carton Size	61.0 * 58.5 * 313cm
Standard Carton Gross Weight	16.0kg



Head Office :1600 AVENUE DE LORIMIER BUREAU, 384 MONTRÉAL (QUÉBEC) CANADA H2K3W8 USAOffice:128 W SUFFLOK AVE,CENTRAL ISLIP,11722 N
Middle east & Africa Office : warehouse 9 /shed 9, Technology park P.O. Box 54806 RAK FZE , UAE



Email Us At:

sales@acculabusa.com middleeast@acculabusa.com



Phone Support:

© Copyright 2014 by ACCULAB_USA - All rights reserved