



HM27

| Humidity & Temperature Meter

☰ Details Info

Specification

| | |
|-----------------------------|-----------------------------|
| Temperature Measuring Range | -10°C~50°C |
| Humidity Measuring Range | 10%RH~99%RH |
| °C/°F Selection | √ |
| Accuracy of temperature | ±1% |
| Accuracy of humidity | ±3%(30~95%) ±5% (10~30%) |

| | |
|------------------------------------|-----------|
| Auto /ManualPower Off | √ |
| Low Battery Indication | √ |
| Data Hold | √ |
| Temperature Resolution | 0.1°C |
| Humidity Resolution | 0.1%RH |
| Sampling Rate | 2time/sec |
| Temperature & Humidity Alarm Setup | -- |
| Max/Min Measurement | -- |
| arge LCD Dual Display | -- |

General Characteristics

| | |
|--------------------|---------------------|
| Power | 9V Alkaline Battery |
| LCD size | 48.3*30mm |
| Product Color | Ivory |
| Product Net Weight | 194g |
| Product Size | 207*70*29mm |



Head Office :1600 AVENUE DE LORIMIER BUREAU, 384 MONTRÉAL (QUÉBEC) CANADA H2K3W8 USAOffice:128 W SUFFLOK AVE,CENTRAL ISLIP,11722 N
Middle east & Africa Office : warehouse 9 /shed 9, Technology park P.O. Box 54806 RAK FZE , UAE



Email Us At:

sales@acculabusa.com middleeast@acculabusa.com



Phone Support: