



IT72D

| Infrared Thermometer

☰ Details Info

Features:

1. Temp. range: -50°C to 650°C (-58°F to 1202°F)
2. Optical resolution: D:S=30:1
3. Adjustable emissivity 0.1~1.0
4. MAX/MIN record
5. Fast response time <250ms
6. Overrange indication
7. Data Hold
8. Auto power off

Specification:

IR Temp Range	-50 °C ~1050 °C/ -58 °F ~ 1922 °F
---------------	--------------------------------------

Basic Accuracy(IR)	-50 °C ~ 0 °C: ± 4 °C 0 °C ~ 1050 °C: $\pm 2\% \pm 2$ °C
Response Time	≤ 250 ms
Emissivity	Adjustable: 0.1~1.0
Optical Resolution	D:S=30:1
Resolution	0.1 °C/ °F
Spectral Response	8 ~ 14um
Diode Laser	Output<1mW, 630 ~ 670nm, class 2(II)
Auto Power Off	Auto shut off after 20 seconds of inactivity
Operating Temp.	0 °C ~ 50 °C / 32 °F ~ 122 °F
Storage Temp.	-20 °C ~ 60 °C / -4 °F ~ 140 °F
Relative Humidity	Operating:10 ~ 95%RH; Storage: <80%RH
Power Supply	9V battery
Dimensions(L*W*H)	155.5*98.8*27.5mm
Weight	172g
Accessories	User's Manual, 9V Battery, carrying case with gift box



Head Office :1600 AVENUE DE LORIMIER BUREAU, 384 MONTRÉAL (QUÉBEC) CANADA H2K3W8 USAOffice:128 W SUFFLOK AVE,CENTRAL ISLIP,11722 N
Middle east & Africa Office : warehouse 9 /shed 9, Technology park P.O. Box 54806 RAK FZE , UAE



Email Us At:

sales@acculabusa.com middleeast@acculabusa.com



Phone Support:

© Copyright 2014 by ACCULAB_USA - All rights reserved