



LM13

| Lux Meter

☰ Details Info

Features:

- 1. Auto revise parameters for nonstandard illumination
- 2. Silicon photo-diode with spectral response filter
- 3. User selectable Lux/Fc
- 4. MAX/MIN record
- 5. Low battery indication
- 6. Auto power off

Specification:

Resolution	0.1
Reading Display Update	2times/second

Operation conditions	-20 °C ~ 60 °C, 10%RH ~ 90%RH
Storage conditions	-20 °C ~ 60 °C, 10%RH ~ 75%RH
Measurement Range	0 Lux ~ 100K Lux, 0Fc ~ 10KFc
Accuracy	±3% rdg±0.5%f.s.(<10,000Lux); ±4% rdg±10dgts.(>10,000Lux)
Discrete Cosine Respond	$f_2' \leq 2\%$
Spectrum Accuracy	$\forall \lambda$ function $f_1' \leq 6\%$
Spectrum Response	CIE(Coherent Infrared Energy)
Size(L*W*H)	172* 55*38mm
Weight	162g
Accessories	User's Manual, Tripod, Battery, Carrying case, Gift box



Head Office :1600 AVENUE DE LORIMIER BUREAU, 384 MONTRÉAL (QUÉBEC) CANADA H2K3W8 USAOffice:128 W SUFFLOK AVE,CENTRAL ISLIP,11722 N
Middle east & Africa Office : warehouse 9 /shed 9, Technology park P.O. Box 54806 RAK FZE , UAE



Email Us At:

sales@acculabusa.com middleeast@acculabusa.com



Phone Support: