



## SM33T sound level meter

---

| Sound level meter

☰ Details Info

### Features:

Performance:meet the requires of GB/T3785-2 and 61672-2

Application:be used for monitoring online environmental noise and automatically measuring the noise of vehicle Inspection.

### Characteristics:

- LCD display
- Data output with the instantaneous sound level,1Lp/s
- AC and DC signal output

### Technical Parameters:

Measuring Range	30dB~130dB
Frequency Range	20HZ~12.5KHz
Frequency weighted	A(weighting),C(weighting)
Time-weighted	F(fast)
Display	Large LCD, background light
Measuring Mode	Lp
output	AC,DC and RS232C
Power supply	4 Batteries, 6V power supply can be connected

Dimensions	230mm×72mm×30mm
Weight	0.3kg



Head Office :1600 AVENUE DE LORIMIER BUREAU, 384 MONTRÉAL (QUÉBEC) CANADA H2K3W8 USAOffice:128 W SUFFLOK AVE,CENTRAL ISLIP,11722 N  
Middle east & Africa Office : warehouse 9 /shed 9, Technology park P.O. Box 54806 RAK FZE , UAE



Email Us At:

[sales@acculabusa.com](mailto:sales@acculabusa.com) [middleeast@acculabusa.com](mailto:middleeast@acculabusa.com)



Phone Support:

---

© Copyright 2014 by ACCULAB\_USA - All rights reserved