



VB3A Vibration Meter

| Detection systems in public places

☰ Details Info

SPECIFICATION

Vibration Meter Measuring Range

Acceleration	0.1-199.9m/S ² peak(rms*v2)
Velocity	0.1-1999.9mm/s rms
Displacement	0.001-1.999mm p-p(rms*2v2)
Accuracy	±5%±2digits

Frequency Response

Acceleration	10Hz-1KHz(LO) 1KHz-15KHz(HI)
Velocity/Displacement	10Hz-1KHz
Data Output	AC Output 2V Peak,Load
Test Mode	Acceleration/Velocity/Displacement
Sampling Rate	1S
Low Battery Indication	√

Auto Power Shut Off	√
Power	9V Battery(6F22)
Battery Life	Continue Using for 25 hours



Head Office :1600 AVENUE DE LORIMIER BUREAU, 384 MONTRÉAL (QUÉBEC) CANADA H2K3W8 USA Office:128 W SUFFLOK AVE,CENTRAL ISLIP,11722 N
Middle east & Africa Office : warehouse 9 /shed 9, Technology park P.O. Box 54806 RAK FZE , UAE



Email Us At:

sales@acculabusa.com middleeast@acculabusa.com



Phone Support:

© Copyright 2014 by ACCULAB_USA - All rights reserved